

Suspended Luminaire

Product Image



Product Image



PC

SMD
2835

PF
> 0.9

CRI
> 82

3000K

4000K

6000K

> 80
LM/W

IP20

3 years
warranty

Product Description

Recessed slim profile luminaire with clear cut lines, providing downward light. Designed to meet architects demands for specific structured surroundings

Product Application

- Reception
- Conference Room
- Call Centre
- Offices

Product Specification	1200MM	1500MM
Voltage:	AC200-240V(50-60Hz)	AC200-240V(50-60Hz)
LED:	Epistar Chip SMD2835	Epistar Chip SMD2835
Material:	Aluminium + PC	Aluminium + PC
Driver:	Lifud driver	Lifud driver
CCT:	3000K/4000K/6500K	3000K/4000K/6500K
Operation temperature:	-20°C~40°C	-20°C~40°C
Installation Way:	Suspended	Suspended
Length:	1200mm	1500mm
Lumen:	>80LM/W	>80LM/W
CRI:	>80	>80
PF:	0.90	0.90

Product Codes

LED	Hilton-1200-Suspended	1200mm	40W	3200LM
LED	Hilton-1500-Suspended	1500mm	50W	4000LM
EM	Add suffix /EM for 3hr Maintained Emergency			
DALI	Add suffix /DALI for Dali Dimming			

Sold in Silver as standard Add suffix /B for Black or /W for White

Supplied With a 1.5 Meter Suspension Kit

Bespoke Lengths & Lumen outputs available on request

Product Dimensions

